

Patent
10/099,891

Listing of Claims:

1. (Original) An optical switch, comprising:
at least one input port for receiving a plurality of channel wavelengths of an optical signal and a plurality of output ports; and
a plurality of wavelength selective elements that each select a channel wavelength from among the plurality of channel wavelengths received at the at least one input port;
a plurality of optical elements respectively associated with said plurality of wavelength selective elements, each of said optical elements directing one of the selected channel wavelengths selected by the associated wavelength selective element to any one of the output ports independently of all other channel wavelengths and with a selectively variable degree of attenuation; and
a controller for adjusting a configuration of the optical elements to provide the channel wavelengths with the selectively variable degree of attenuation.
2. (Original) The optical switch of claim 1 further comprising a monitoring arrangement for determining a power level of a given channel wavelength received in the at least one input port relative to a power level of said given channel wavelength received in one of the output ports.
3. (Original) The optical switch of claim 1 further comprising a monitoring arrangement for determining respective power levels of the plurality of channel wavelengths received in the at least one input port relative to respective power levels of the plurality of channel wavelengths received in the output ports.
4. (Original) The optical switch of claim 2 wherein said monitoring arrangement comprises:
at least one monitoring port receiving a portion of optical power at each of the channel wavelengths from the at least one input port;

Patent
10/099,891

at least one detector associated with at least one of said wavelength selective elements for measuring a power level of an optical signal incident thereon, said detector being positioned to receive from the monitoring port the portion of optical power at the channel wavelength selected by the associated wavelength selective element .

5. (Original) The optical switch of claim 3 further comprising a plurality of input ports and wherein said monitoring arrangement comprises:

a plurality of monitoring ports each receiving a portion of optical power at each of the channel wavelengths from one of the input ports;
a plurality of detectors each associated with one of the plurality of wavelength selective elements for measuring a power level of an optical signal incident thereon, said detectors being positioned to respectively receive from the monitoring port the portion of optical power at the channel wavelength selected by the associated wavelength selective element.

6. (Original) The optical switch of claim 4 wherein said optical elements each include a collimating lens and a tiltable mirror.

7. (Original) The optical switch of claim 5 wherein said optical elements each include a collimating lens and a tiltable mirror.

8. (Original) The optical switch of claim 6 wherein said detector is positioned so that said received portion of the given channel wavelength does not traverse said collimating lens.

9. (Original) The optical switch of claim 7 wherein said detectors are positioned so that the portion of the selected channel wavelengths received from the monitoring ports does not traverse said collimating lens.

10. (Original) The optical switch of claim 1 wherein said configuration of the optical elements adjusted by the controller is a position of the optical elements.

**Patent
10/099,891**

11. (Original) The optical switch of claim 6 wherein said configuration of the optical elements adjusted by the controller is a position of the tiltable mirror.

12. (Original) The optical switch of claim 1 wherein at least one of the optical elements includes a shutter for attenuating the selected channel wavelength directed by the optical element, and wherein said configuration of the optical elements adjusted by the controller includes a position of the shutter within a path traversed by the selected channel wavelength.

13. (Original) The optical switch of claim 1 further comprising a free space region disposed between the input ports and the output ports.

14. (Original) The optical switch of claim 4 further comprising a free space region disposed between the input ports and the wavelength selective elements.

15. (Original) The optical switch of claim 1 wherein said optical elements retroreflect said channel wavelengths.

16. (Original) The optical switch of claim 4 wherein said wavelength selective elements are thin film filters each transmitting therethrough a different one of the channel wavelengths and reflecting the remaining channel wavelengths.

17. (Original) The optical switch of claim 4 wherein said optical elements are reflective mirrors that are selectively tiltable in a plurality of positions such that in each of the positions the mirrors reflect the channel wavelength incident thereon to any selected one of the output ports.

18. (Original) The optical switch of claim 1 wherein the configuration of the optical elements adjusted by the controller includes a position of the optical elements.

Patent
10/099,891

19. (Original) The optical switch of claim 17 wherein the configuration of the optical elements adjusted by the controller includes the position of the reflective mirrors.

20. (Original) The optical switch of claim 17 wherein said reflective mirrors are part of a micro-electromechanical (MEM) retroreflective mirror assembly.

21. (Original) The optical switch of claim 17 wherein said reflective mirrors are part of a retroreflective optical assembly.

22. (Original) The optical switch of claim 17 wherein said reflective mirrors each include a piezoelectric actuator.

23. (Original) The optical switch of claim 14 wherein said free space region comprises an optically transparent substrate having first and second parallel surfaces, said wavelength selective element includes a plurality of wavelength selective elements arranged in first and second arrays extending along the first and second parallel surfaces, respectively.

24. (Original) The optical switch of claim 23 wherein the optically transparent substrate includes air as a medium in which the optical signal propagates.

25. (Original) The optical switch of claim 23 where the optically transparent substrate is silica glass.

26. (Original) The optical switch of claim 23 wherein said first and second arrays are laterally offset with respect to one another.

**Patent
10/099,891**

27. (Original) The optical switch of claim 26 wherein each of said wavelength selective elements arranged in the first array direct the selected channel wavelength to another of said wavelength selective elements arranged in the second array.

28. (Original) The optical switch of claim 4 further comprising a collimating lens disposed between each one of said wavelength selective elements and the optical element associated therewith, each of said optical elements being positioned at a focal point of the lens associated therewith.

29. (Original) The optical switch of claim 28 wherein said collimating lens and said optical element serve as a retroreflector.

30. (Original) An optical amplifier system for amplifying with a prescribed gain at least one channel wavelength of a WDM optical signal, said optical

BEST AVAILABLE COPY